


Submittal: DWPMZPC08A



STRONG-POINT[®] PANCAKE HEAD, ZINC PLATED

Size	Part#	Case Qty.	Description
10-12 x 1	108PC	5M	Phillips Pancake Head, Zinc Plated
10-12 x 1-1/2	112PC	3M	Phillips Pancake Head, Zinc Plated

Application: Attaches panel clips to wood.

- Specifications:
- Meets ASTM¹ A 510 for carbon steel manufacturing
 - Meets ASTM B 633 for electrodeposited zinc coatings
 - Meets ASTM F1941 for corrosion resistance

- Features:
- Multipurpose sheet metal screw for light to medium gauge applications
 - 22° point pierces light gauge metal
 - Twin fast thread design creates faster installation speeds

Installation: A standard screw gun with torque limiting nose piece set at a maximum of 3000 RPM drive speed recommended. Use a #2 reduced Phillips drive bit. Do not over torque as it can cause the head to snap, stripping of the recess, or damage to the work surface.

Pullout Values (Avg. Lbs.)					
Fastener	Wood Embedment				
	1/2" PLY	5/8" PLY	3/4" PLY	YELLOW PINE	3/4" OSB
10-12	357	375	396	572	278

The values listed are averages achieved under laboratory conditions and imply no warranty. Appropriate safety factors should be applied to these values for design purposes.

¹(American Society of Testing Materials)