


Submittal: SD410EM0808BH



STRONG-POINT[®] 410 STAINLESS STEEL PHILLIPS MODIFIED TRUSS (R/W) HEAD, PASSIVATED & WAXED

Size	Part#	Pt.	Case Qty.	Description
8-18 x 1/2	4M82	2	5M	410 Stainless Steel Phillips Modified Truss (R/W) Head, Passivated & Waxed
8-18 x 3/4	4M83	2	5M	410 Stainless Steel Phillips Modified Truss (R/W) Head, Passivated & Waxed
8-18 x 1	4M84	2	4M	410 Stainless Steel Phillips Modified Truss (R/W) Head, Passivated & Waxed
8-18 x 1-1/4	4M85	2	3M	410 Stainless Steel Phillips Modified Truss (R/W) Head, Passivated & Waxed
8-18 x 1-5/8	4M87	2	3M	410 Stainless Steel Phillips Modified Truss (R/W) Head, Passivated & Waxed
8-18 x 1-7/8	4M88	2	2M	410 Stainless Steel Phillips Modified Truss (R/W) Head, Passivated & Waxed
8-18 x 2-1/2	4M92	2	1.5M	410 Stainless Steel Phillips Modified Truss (R/W) Head, Passivated & Waxed
8-18 x 3	4M95	2	1.5M	410 Stainless Steel Phillips Modified Truss (R/W) Head, Passivated & Waxed

Application: Attaches metal to metal.
Drill Capacity (in.): .035 - .100

- Specifications:
- Manufactured to SAE¹ J78 for dimensional specifications
 - Meets F.I.P.²-1000.7 for torsional strength and drill speed
 - Medium degree of corrosion resistance

Installation: A standard screw gun with torque limiting nose piece set at a maximum of 2500 RPM drive speed recommended. Use a #2 reduced Phillips drive bit. Do not over torque as it can cause the head to snap or stripping of the recess. Installed fasteners must penetrate a minimum of three full threads beyond the metal structure.

Pullout Values (Avg. Lbs.)									
Fastener		Steel Gauge							
Size	Pt.	22	20	18	16	14	12	1/8	3/16
8-18	2	260	292	479	685	933	1533		

Shear Values (Avg. Lbs.)									
Fastener		Steel Gauge (Lapped)							
Size	Pt.	22	20	18	16	14	12	1/8	3/16
8-18	2	546	721	1031	1049				

The values listed are averages achieved under laboratory conditions and imply no warranty. Appropriate safety factors should be applied to these values for design purposes.

¹(Society of Automotive Engineers)

²(Fastener Inspection Products)