

Submittal: CSHWH320BC



STRONGCON[®] SLOTTED INDENTED HEX WASHER HEAD, HI-LOW, NOTCHED THREADS, DIAMOND POINT, CERAMIC COATING

Size	Part#	Case Qty.	Description
3/16 x 1-1/4	CH320	5M	Slotted Indented Hex Washer Head, Hi-Low, Notched Threads, Diamond Point, Ceramic Coating
3/16 x 1-3/4	CH328	3M	Slotted Indented Hex Washer Head, Hi-Low, Notched Threads, Diamond Point, Ceramic Coating

Application: Attaches wood or metal to concrete, brick, cement block or masonry.

Specifications:

- Meets ASTM¹ A 510 for carbon steel manufacturing
- Product meets ASTM B-117 for salt spray corrosion testing

Features:

- Ceramic coating exceeds 500/hr. salt spray resistance
- Designed to work with ACQ, pressure, and fire treated lumber
- Notched threads for cutting into concrete, brick and cement block
- Diamond Point design for cutting and clearing debris during installation

Installation: Using a 5/32 carbide masonry drill bit and hammer drill (in hammer mode), drill a hole 1/4" deeper than the minimum embedment requirements of the concrete screw to be installed*. Clean the dust from the hole using compressed air or hand pump. Use a 1/4" nut setter with hammer mode turned OFF or a standard rotary drill to install fastener until seated. Do not over torque as it can cause the head to snap or stripping of the recess.

*When installing into Hollow Block CMU drill through the full thickness of face wall.

Allowable Load Capacities (Avg. Lbs.)					Structural Properties (ksi)		Spacing
Substrate: Concrete			3,000 PSI				
Size	Min. Embed	Min. Edge Dist.	Tension	Shear	Fu	Fy	Spacing
3/16	1"	2-1/2"	151	255	70	52	3"

The values listed are averages achieved under laboratory conditions and imply no warranty. Appropriate safety factors should be applied to these values for design purposes.

¹(American Society of Testing Materials)