INTERCORP

STRONG-POINT®
Get the Point. Strong-Point.

Submittal: SDWSWH1212Z



STRONG-POINT® UNSLOTTED INDENTED HEX WASHER HEAD, ZINC PLATED W/BONDED NEO-EPDM WASHER

Size	Part#	Pt.	Case Qty.	Description
12-14 x 3/4	HA1212	3	3M	Unslotted Indented Hex Washer Head, Zinc Plated w/Bonded NEO-EPDM Washer
12-14 x 1	HA1216	3	3M	Unslotted Indented Hex Washer Head, Zinc Plated w/Bonded NEO-EPDM Washer
12-14 x 1-1/4	HA1220	3	2.5M	Unslotted Indented Hex Washer Head, Zinc Plated w/Bonded NEO-EPDM Washer
12-14 x 1-1/2	HA1224	3	2M	Unslotted Indented Hex Washer Head, Zinc Plated w/Bonded NEO-EPDM Washer

Application: Attaches metal to metal.

Drill Capacity (in.): .035 - .210

Specifications:

- Meets ASTM[1] C 1513 for cold-formed steel framing connections
- Meets ASTM A 510 for carbon steel manufacturing
- Manufactured to SAE[2] J78 for dimensional specifications
- Meets F.I.P.[3]-1000.7 for torsional strength and drill speed
- Meets ASTM F1941 for corrosion resistance
- ICC-ES Evaluation Report: ESR-3528

Installation: A 5/16" hex nut setter or 5/16" drive socket with torque limiting nose piece set at a maximum of 2000 RPM drive speed recommended. Do not over torque as it can cause the head to snap or stripping of the threads. Installed fasteners must penetrate a minimum of three full threads beyond the metal structure.

Pullout Values (Avg. Lbs.)									
Fastener		Steel Gauge							
Size	Pt.	22	20	18	16	14	12	1/8	3/16
12-14	3	283	333	537	737	1034	1585	2349	2911

Shear Values (Avg. Lbs.)									
Fastener		Steel Gauge (Lapped)							
Size	Pt.	22	20	18	16	14	12	1/8	3/16
12-14	3		749	1320	1574	1914	1929		

The values listed are averages achieved under laboratory conditions and imply no warranty. Appropriate safety factors should be applied to these values for design purposes.

[1](American Society of Testing Materials)

[2](Society of Automotive Engineers)

[3](Fastener Inspection Products)

Los Angeles 800.762.2004 | New York 888.322.2262 | Chicago 800.533.9669 | Dallas 800.558.7222 | Atlanta 800.822.9690 | Portland 800.434.5606 | Houston 800.558.7222 | Cleveland 800.533.9669 | Miami 800.822.9690