

**Submittal:** NPSHZ10085Z



**STRONG-POINT<sup>®</sup> SLOTTED INDENTED HEX WASHER HEAD, ZINC PLATED**

Size	Part#	Case Qty.	Description
10 x 1/2	N10085	10M	Slotted Indented Hex Washer Head, Zinc Plated
10 x 3/4	N10125	8M	Slotted Indented Hex Washer Head, Zinc Plated
10 x 1	N10165	5M	Slotted Indented Hex Washer Head, Zinc Plated
10 x 1-1/2	N10245	3M	Slotted Indented Hex Washer Head, Zinc Plated
10 x 2	N10325	2M	Slotted Indented Hex Washer Head, Zinc Plated
10 x 3	N10485	1.5M	Slotted Indented Hex Washer Head, Zinc Plated

**Application:** Attaches light gauge sheet metal to sheet metal or wood.

- Specifications:**
- Meets ASTM<sup>1</sup> A 510 for carbon steel manufacturing
  - Meets ASTM B 633 for electrodeposited zinc coatings
  - Meets ASTM F1941 for corrosion resistance

- Features:**
- Multipurpose sheet metal screw for light to medium gauge applications
  - 22° point pierces light gauge metal
  - Twin fast thread design creates faster installation speeds

**Installation:** A 5/16" hex nut setter or 5/16" drive socket with torque limiting nose piece set at a minimum of 1400 RPM drive speed recommended. Do not over torque as it can cause the head to snap or stripping of the threads. Installed fasteners must penetrate a minimum of three full threads beyond the metal structure.

<sup>1</sup>(American Society of Testing Materials)