


**Submittal:** NPUHZ1012Z



**STRONG-POINT UNSLOTTED INDENTED HI-HEX WASHER HEAD, FINE THREAD, RAZOR POINT, ZINC PLATED**

Size	Part#	Case Qty.	Description
10-24 x 3/4	NU1012H	5M	Unslotted Indented Hi-Hex Washer Head, Fine Thread, Razor Point, Zinc Plated

**Application:** Attaches light gauge sheet metal to sheet metal.

- Specifications:**
- Meets ASTM<sup>1</sup> A 510 for carbon steel manufacturing
  - Meets ASTM B 633 for electrodeposited zinc coatings
  - Meets ASTM F1941 for corrosion resistance

- Features:**
- Multipurpose sheet metal screw for light to medium gauge applications
  - 20° point pierces light gauge metal quickly
  - Razor non-walking point for faster engagement
  - Hi-Hex head provides deeper tool engagement for improved drivability

**Installation:** A 5/16" hex nut setter or 5/16" drive socket with torque limiting nose piece set at a minimum of 2450 RPM drive speed recommended. Do not over torque as it can cause the head to snap or stripping of the threads. Installed fasteners must penetrate a minimum of three full threads beyond the metal structure.

<sup>1</sup>(American Society of Testing Materials)