


**Submittal:** PGWSW17165SSC



**STRONG-POINT<sup>®</sup> UNSLOTTED INDENTED HEX FLANGE WASHER HEAD W/WASHER, TYPE AB, STRONG-SHIELD COATED**

Size	Part#	Case Qty.	Description
17-14 x 1	PGA17165	2M	Unslotted Indented Hex Flange Washer Head w/Washer, Type AB, Strong-Shield Coated

Application: Attaches metal to wood. Used in roofing and siding applications.

- Specifications:
- Meets ASTM<sup>1</sup> A 510 for carbon steel manufacturing
  - Product meets ASTM B-117 for salt spray corrosion testing

- Features:
- Strong-Shield coating exceeds 1,000/hr. salt spray resistance - Kesternich: 15 cycles
  - Rust/Acid rain protection
  - Designed to work with ACQ treated lumber



Coating: The Strong-Shield coating is a high-grade metal surface processing technology that prevents corrosion. The system consists of four layers: a metallic zinc layer, a hex-chromium passivation, a layer of functional nano coating used as a sealer, and a high-grade anti-corrosion chemical conversion film.

Installation: A 5/16" hex nut setter or 5/16" drive socket with torque limiting nose piece set at a maximum of 2500 RPM drive speed recommended. The fastener is completely installed when it is embedded a minimum of 1/2" into substrate. Do not over torque as it can cause the head to snap, or damage to the work surface.

Pullout Values (Avg. Lbs.)					
Fastener	Steel Gauge				
Size	26	24	22	20	18
17-14	222	359	491	438	549

Shear Values (Avg. Lbs.)					
Fastener	Steel Gauge (Lapped)				
Size	26	24	22	20	18
17-14	454	739	884	953	1312

The values listed are averages achieved under laboratory conditions and imply no warranty. Appropriate safety factors should be applied to these values for design purposes.

<sup>1</sup>(American Society of Testing Materials)